



* Le immagini sono solo illustrative / Images are illustrative only

WMS 40

FONTANELLA PENSILE	WALL MOUNT FOUNTAIN	FONTAINE MURALE	
Fontanelle refrigeranti con serbatoio di accumulo	Drinking water fountains with tank	Fontaines réfrigérantés avec réservoir	
Sistema di raffreddamento: sistema con serbatoio INOX AISI 304 ermetico	Cooling system: cooling system with hermetic tank in STAINLESS STEEL AISI 304	Système de refroidissement: système avec reservoir hermétique en INOX AISI 304	
Sistema di erogazione: a pulsante	Dispensing system: push botton	Système de distribution: poussoir	
Produzione d'acqua fredda	Delivery of cold water	Débit d'eau froide	38 ÷ 45 l/h
Capacita' serbatoio	Tank capacity	Capacité de réservoir	4 l
Assorbimento	Absorption	Absorption	102 W
Potenza frigorifera	Cooling power	Puissance de réfrigération	282 W
Pressione di esercizio	Operating pressure	Pression de fonctionnement	3,5 bar
Alimentazione	Power supply	Alimentation	230 V – 50 Hz
Compressore	Compressor	Compresseur	1/12 HP
Gas R290	Gas R290	Gas R290	28 g
Rumorosità	Noise	Bruit	<67 db.
Dimensioni (mm)	Dimensions (mm)	Dimensions (mm)	320 x 380 x 580h
Peso	Weight	Poids	28 kg
Pannelli	Panels	Panneaux	Skinplated or
Pannelli opzionali	Optionals Panels	Panneaux facultatif	Stainless steel
Lavello	Sink	Évier	Stainless steel AISI 304
Voltaggi speciali	Special voltages	Voltages spéciaux	Upon request
Allestimenti personalizzati	Personalized equipment	È quipements personnalisés	Upon request